



Product Catalog

Flexibility
to choose
the right
chargers
for your
property.

All our products & services are
100% open-standards (OCPP)
compliant - avoiding vendor
lock-in or stranded assets.

Each EV charger we offer
has been rigorously tested
to ensure it can deliver the
performance and reliability
you can count on.



Level 2 Chargers

With their wide range of features and affordable price point, Level 2 chargers are the ideal choice for most multi-residential and commercial situations.

Joint Tech EVH Series

Supply Input	208/240 V
Current	32 or 48 A
Derated Output Current	10, 16, 24, 32 A
Protection Rate	NEMA 4, IK08
Warranty	3 years included
Cable	5.5m (18ft), 7.6m (25ft)
Display	LED indication
ISO15118/PNC Ready	Yes



LG Electronics

Supply Input	208/240 V
Current	48 A
Derated Output Current	16, 24, 32, 40 A
Protection Rate	NEMA 3R, IK10, IP55
Warranty	3 years included
Cable	7m (23ft)
Display	14 segment LED
ISO15118/PNC Ready	No



LITE-ON IC3

Supply Input	208/240 V
Current	32 or 80 A
Derated Output Current	Configurable from 6A and up to rated current
Protection Rate	NEMA-4 (IP66), IK10
Warranty	3 years included
Cable	5.5 m (18 ft)
Display	Dot-matrix (2 lines)
ISO15118/PNC Ready	No



Wallbox Pulsar Pro

Supply Input	240/208 V
Current	48A
Derated Output Current	Configurable from 6A and up to rated current
Protection Rate	NEMA-4
Warranty	3 years included
Cable	5.5m (18 ft) & 7.5m (25ft)
Display	RGB LED halo on charger
ISO15118/PNC Ready	Yes



Zerova AX Series

Supply Input	208/240 V
Current	48 or 80 A
Derated Output Current	Configurable from 6A and up to rated current
Protection Rate	NEMA-4
Warranty	2 years included
Cable	5m (16.4ft),
Display	5" LCD
ISO15118/PNC Ready	Yes



DC Fast Chargers

If your customers are parked for shorter amounts of time (ie: public retail), DC Fast chargers are a great option.

ABB Terra Series

Power	90 kW; 120 or 2x60 kW; 180 or 2x90 kW
Input Voltage	480Y / 277 VAC +/- 10 % (60 Hz)
Simultaneous Ch.	Yes
Protection Rate	NEMA-3R (IP54)
Warranty	2 years included
Cable	20 ft
ISO15118/PNC Ready	Yes



Zerova DS Series

Power	60, 90, 120, 150, or 180 kW
Input Voltage	480V 3Ph VAC
Simultaneous Ch.	Yes
Protection Rate	NEMA 3R; IK10
Warranty	2 years included
Cable	15 or 23 ft
ISO15118/PNC Ready	Yes



LG Electronics

Power	150kW
Input Voltage	480V 3P VAC (60Hz)
Simultaneous Ch.	Yes
Protection Rate	IP55, NEMA 3R, IK10
Warranty	2 years included
Cable	18 ft (5.5 m)
ISO15118/PNC Ready	Yes



XCharge C6AM

Power	40, 50, 75, 100, 150, or 200 kW
Input Voltage	3-phase 480VAC ± 10% 60Hz
Simultaneous Ch.	Yes
Protection Rate	IP54, IK10
Warranty	3 years included
Cable	15ft
ISO15118/PNC Ready	Yes



Pedestals, signs, and more - we've got you covered.

It's not just about the chargers and the network: the right accessories can make or break a smooth installation. SWTCH ensures you have everything you need including:

- Networking Hardware
- Pedestal & Cable Management
- Signage



SWTCH Control™ Load Management for Smarter, More Affordable EV Charging

SWTCH Control™ intelligently distributes energy to your chargers based on the real-time capacity available on the circuit, panel, and/or building. This effectively allows you to install up to 20x more chargers with minimal or no costly electrical upgrades, all while ensuring EV drivers still get the charge they need while plugged in.

We've done
the work,
so you don't
have to.

Our deep understanding and rigorous process in selecting our EV charging hardware ensures our solution is tailored and flexible to meet the unique needs of your property, today and for years to come.



Connect with us.

Let's get started with a complimentary consultation. We'll walk you through the ins and outs of EV charging and ensure you get the right system for your property.

Email us today at
sales@swtchenergy.com.

[SWTCHENERGY.COM](https://www.swtchenergy.com)